

# SCREWING TECHNOLOGY BATTERY TYPE

**BAHCO**  
DORTMUND



## CORDLESS SCREWDRIVER

---

# BAHCO

**EY 6220 NQ**

- 2.5 Ah Ni-MH high-performance rechargeable battery
- Low weight of 0.43 kg (incl. battery)
- ¼ inch hexagon socket
- Two speed gearbox
- Gear lock for manual tightening
- Right/left hand rotation
- Easy changeover from stick to pistol shape
- Incl. one battery



**TECHNISCHE DATEN**

Voltage	Charging time	Speed w/o. Load min <sup>-1</sup>		Max. Torque [Nm]	Torque range	Clutch-torque [Nm]	Weight incl. battery kg
		Low	High				
2.4	45 full charge	200	600	2,9	mehrere	ca. 0.4 - 2.0	0.43

**EY 7410 LA2S**

- 1.5 Ah Li-ion battery
- Low weight of 0.5 kg (incl. battery)
- Counting function of the screwing operations
- ¼ inch hexagon socket
- 21-step clutch
- Electronic shut-off
- LED light
- incl. one rechargeable battery



**TECHNICAL DATA**

Voltage	Charging time	Speed w/o. Load min <sup>-1</sup>		Max. Torque [Nm]	Torque range	Clutch-torque [Nm]	Weight incl. battery kg
		Low	High				
3.6	30 full charge	200	600	4.4	21	ca. 0.3 - 2.9	0.5

## EY 7411 LA1S

- 1.5 Ah Li-ion battery
- Low weight of 0.5 kg (incl. battery)
- Counting function of the screwing operations
- ¼ inch hexagon socket
- 21-step clutch
- Electronic shut-off
- LED light, incl. one rechargeable battery



### TECHNICAL DATA

Voltage	Charging time	Speed w/o. Load min <sup>-1</sup>		Max. Torque [Nm]	Torque range	Clutch-torque [Nm]	Weight incl. battery kg
		Low	High				
3.6	30 full charge	200	600	4.4	21	ca. 0.3 - 2.9	0.5

**BAHCO**  
DORTMUND

**BAHCO GmbH & Co.KG**

Martener Hellweg 60  
DE- 44379 Dortmund

**Telefon**

+49 231/91 72 11-0

**Telefax**

+49 231/91 72 11-22

[www.bahco.de](http://www.bahco.de)

[info@bahco.de](mailto:info@bahco.de)

**BAHCO**

All information subject to change without further notice.  
No responsibility is taken for the correctness of the named specifications.