

# SCREWING TECHNOLOGY BATTERY TYPE

**BAHCO**  
DORTMUND



## CORDLESS DRILL & SCREWDRIVER

---

**BAHCO**

**EY 74A2 X/XT/PN2G/LJ2G**

- Brushless high-performance motor
- Hybrid switch, soft start
- Extremely hard chucks
- Battery charge level indicator with LED light
- Compact housing (178 mm), carbon design



**TECHNICAL DATA**

Voltage	Charging time	Speed w/o. Load min <sup>-1</sup>		Max. Torque [Nm]		Torque range	Weight incl. battery
		Low	High	Soft	Hard		
Volt	min.					+ Drill path	kg
18	65 / 80	20-480	70-1580	32	50	18	2.05

**EY 74A3 X/XT/PN2G/LJ2G**

- Brushless high-performance motor
- Thread-cutting function
- Hybrid switch, soft start
- Extremely hard chucks
- Battery charge level indicator with LED light
- Compact housing (160 mm), carbon design



**TECHNICAL DATA**

Voltage	Charging time	Speed w/o. Load min <sup>-1</sup>		Max. Torque [Nm]		Torque range	Weight incl. battery
		Low	High	Soft	Hard		
Volt	min.					+ Drill path	kg
18	65 / 80	20-530	70-1800	32	50	18	2.00

**EY 7441 X/LF2S/LH2S**

- Low weight from 1.70 kg (incl. battery)
- 18-stage clutch plus drill speed
- 13 mm high-performance drill chuck (keyless)
- Electronic speed stabilisation
- Electronic start-up brake, right/left rotation
- Safe front handle and LED light
- Without batteries and charger



**TECHNICAL DATA**

Voltage	Charging time	Speed w/o. Load min <sup>-1</sup>		Max. Torque [Nm]		Torque range	Weight incl. battery
		Low	High	Soft	Hard		
Volt	min.					+ Drill path	kg
14.4	45 / 65	70-400	200-1400	28	41.5	18	from 1.7

## EY 7450 X/XT

- Low weight of 2.15 kg (incl. battery)
- 13 mm heavy-duty drill chuck (keyless)
- Electric speed stabilisation
- Electronic run-out brake
- Right/left rotation
- Compact housing and LED light



### TECHNICAL DATA

Voltage	Charging time	Speed w/o. Load min <sup>-1</sup>		Max. Torque [Nm]		Torque range + Drill path	Weight incl. battery kg
		Low	High	Soft	Hard		
18 Volt	65 / 80 min.	50-430	160-1.650	40	57	18	1,6

## EY 7451 X/PN2S

- Low weight of 1.60 kg (incl. battery)
- 13 mm heavy-duty drill chuck (keyless)
- Electric speed stabilisation
- Electronic run-out brake
- Right/left rotation
- Compact housing and LED light



### TECHNICAL DATA

Voltage	Charging time	Speed w/o. Load min <sup>-1</sup>		Max. Torque [Nm]		Torque range + Drill path	Weight incl. battery kg
		Low	High	Soft	Hard		
18 Volt	45 / 60 min.	70-400	200-1.400	26	40	18	1,6

## BATTERIES AND CHARGING SYSTEMS



### EY 0L82 B

- 14.4 - 28.8 volt quick charging system  
incl. 14.4 V / 1.5 Ah for all Li-Ion battery types

18 V

5,0 Ah



### EY 9L54 B

- Battery 18 Volt
- Li-Ionen-battery with 5,0 Ah (according to IEC)

18 V

3,0 Ah



### EY 9L53 B

- Battery 18 Volt
- Li-Ionen-battery with 3,0 Ah (according to IEC)

**BAHCO**  
DORTMUND

**BAHCO GmbH & Co.KG**

Martener Hellweg 60  
DE- 44379 Dortmund

**Phone**

+49 231/91 72 11-0

**Fax**

+49 231/91 72 11-22

[www.bahco.de](http://www.bahco.de)

[info@bahco.de](mailto:info@bahco.de)

**BAHCO**

All information subject to change without further notice.  
No responsibility is taken for the correctness of the named specifications.