

# DRILLING MACHINES

**BAHCO**  
DORTMUND



**DRILLING MACHINES  
VERTICAL - VERSION  
SERIES FRD**

**BAHCO**



**BAHCO GmbH & Co.KG**

Martener Hellweg 60

DE- 44379 Dortmund

**Phone**

+49 231/91 72 11-0

**Fax**

+49 231/91 72 11-22

www.bahco.de

info@bahco.de

The drills are light but robust. Their practical design is the result of the latest drilling machine technology.

We offer a complete range of drills with a drilling capacity from 19 mm up to 50 mm.

**TECHNICAL DATA**

Model	Drill. capacity		Torque	Idle speed	Cone	Feed length	Capacity	Total length	Weight	Max. air consumption
	Drill.	Reaming Thread cutting								
Self-closing rotary valve	mm	mm	Nm	min <sup>-1</sup>	MK#	mm	kW	mm	kg	m <sup>3</sup> /min
FRD-20R-21S	19	16	63.7	600	2	67	0.88	282	7.0	1.20
FRD-20R-22S	19	16	63.7	600	3	67	0.88	307	7.0	1.20
FRD-23R-21S	22	19	78.4	480	2	67	0.88	282	7.3	1.20
FRD-23R-22S	22	19	78.4	480	3	67	0.88	307	7.4	1.20
FRD-25R-11S	25	22	147.0	530	3	96	2.10	353	14.0	3.20
FRD-28R-11S	28	25	177.0	430	3	96	2.10	353	14.0	3.20
FRD-32R-11S	32	25	196.0	380	3	96	2.10	353	14.5	3.20
FRD-32R-12S	32	25	196.0	380	4	96	2.10	353	14.5	3.20
FRD-50R-11S *	50	50	431.0	150	4	93	1.80	446	18.7	3.20

\* Special model edition = on request!

Compressed air connection: 1/2" BSP.

Hose size: FRD-20R up to 23R: 1/2", FRD-25R up to 50R: 3/4"

**BAHCO**

All information subject to change without further notice.  
No responsibility is taken for the correctness of the named specifications.