

# PNEUMATIC SCREWDRIVER

**BAHCO**  
DORTMUND



**IMPULSE WRENCH IPW & IPS  
WITH NON SHUT-OFF**

**BAHCO**

The impulse wrenches are equipped without adjustable shut-off control, with double chamber motor and double blade impulse unit. The IPW and IPS series contribute to high productivity and improved quality in many industries.

The impulse wrenches have low reaction forces and can generate high torques without special support.

## STRAIGHT VERSION



### Dimensions

Type	Square drive	Screw size	Torque (5-6bar)	Free speed	Overall length	Weight
	Inch	mm	Nm	min <sup>-1</sup>	mm	kg
<b>with square drive</b>						
IPW-2322N	3/8"	5 - 6	13 - 22	5000	205	0.62
IPW-2335N	3/8"	6 - 8	22 - 35	6400	208	0.74
IPW-2350N	3/8"	8 - 10	32 - 50	6700	209	0.77
IPW-2360N	3/8"	10	40 - 60	5800	223	0.87
IPW-2370N	3/8"	10	40 - 70	5800	247	1.20
IPW-2480N	1/2"	10 - 12	50 - 80	5800	247	1.25
<b>with quick change chuck</b>						
IPS-2220N	1/4"	5 - 6	11 - 20	5000	209	0.62
IPS-2228N	1/4"	6 - 8	18 - 28	6400	214	0.74
IPS-2235N	1/4"	8 - 10	22 - 35	6700	212	0.77
IPS-2240N	1/4"	10	25 - 40	5600	223	0.87

Compressed air connection: 1/4" PT

Hose size: IPW-2322N/2335N as well as IPS-2220N/2228N = 6.5 mm

Hose size: IPW-2350N-2480N as well as IPS-2235N/2240N = 8.0 mm

Noise level: 75 - 84 dB(A)

## PISTOL VERSION



### Dimensions

Type	Square drive	Screw size	Torque (5-6bar)	Free speed	Overall length	Weight
	Inch	mm	Nm	min <sup>-1</sup>	mm	kg
<b>with square drive</b>						
IPW-2312PN	3/8"	5 - 6	6 - 12	3.800	133	0,70
IPW-2322PN	3/8"	6	13 - 22	6.100	133	0,70
IPW-2335PN	3/8"	6 - 8	20 - 35	6.400	140	0,77
IPW-2350PN	3/8"	8 - 10	30 - 50	7.000	140	0,82
IPW-2360PN	3/8"	8 - 10	40 - 60	5.700	153	0,95
IPW-2370PN	3/8"	12	40 - 70	5.600	163	1,15
IPW-2480PN	1/2"	10 - 12	50 - 80	5.600	163	1,17
IPW-2495PN	1/2"	12	75 - 95	5.000	170	1,30
IPW-24125PN	1/2"	12 - 14	90 - 125	4.600	177	1,66
IPW-24160PN	1/2"	14	100 - 160	4.000	197	2,30
<b>with quick change chuck</b>						
IPS-2212PN	1/4"	5 - 6	6 - 12	3.800	133	0,70
IPS-2220PN	1/4"	6	11 - 20	6.100	137	0,70
IPS-2228PN	1/4"	6 - 8	16 - 28	6.400	137	0,77
IPS-2235PN	1/4"	8	20 - 35	7.000	146	0,82
IPS-2240PN	1/4"	8 - 10	30 - 40	5.600	153	0,95

Compressed air connection: 1/4" PT

Hose size: IPW-2312PN-2335PN as well as IPS-2212PN-2228PN = 6.5 mm

Hose size: IPW-2350PN-24125PN as well as IPS-2235PN-2240PN = 8.0 mm

Hose size: IPW-24160PN = 12.7 mm

Noise level: 75 - 84 dB(A)

**BAHCO**  
DORTMUND

**BAHCO GmbH & Co.KG**

Martener Hellweg 60  
DE- 44379 Dortmund

**Phone**

+49 231/91 72 11-0

**Fax**

+49 231/91 72 11-22

[www.bahco.de](http://www.bahco.de)

[info@bahco.de](mailto:info@bahco.de)

**BAHCO**

All information subject to change without further notice.  
No responsibility is taken for the correctness of the named specifications.