

FRH SERIES

BAHCO
DORTMUND



RIVETING HAMMERS SERIES FRH

With these riveting hammers controlled strokes for the rivets can be generated in order to reduce the effect of work hardening of the rivets or damage to the surrounding metal.

These tools can be easily equipped with suitable chisels for other work, such as cutting, splitting, shearing, punching and gouging.

BAHCO

BAHCO GmbH & Co.KG

Martener Hellweg 60

DE- 44379 Dortmund

Phone

+49 231/91 72 11-0

Fax

+49 231/91 72 11-22

www.bahco.de

info@bahco.de



FRH-3-1



FRH-6-2

Riveting and Chisel

Type	Chisel-shaft	Chisel shaft size	Strokes	Piston Ø	Stroke	Total length	Weight	Air cons. (under load)	Comp. air connect.	Hose width	
		mm	Hz	mm	mm	mm	kg	m³/min	BSP	mm	Inch
FRH-3-1	Hex	S 8,7 x 30	60	14,3	38,0	140	1,1	0,35	¼	9,5	¾
FRH-3-2	round	R10,2 x 30	60	14,3	38,0	140	1,1	0,35	¼	9,5	¾
FRH-6-1	Hex	S 8,7 x 30	30	12,7	100,0	206	1,4	0,35	¼	9,5	¾
FRH-6-2	round	R10,2 x 30	30	12,7	100,0	206	1,4	0,35	¼	9,5	¾
FRH-6A-1	Hex	S 8,7 x 30	50	20,0	44,5	193	1,5	0,40	¼	9,5	¾
FRH-6A-2	round	R10,2 x 30	50	20,0	44,5	193	1,5	0,40	¼	9,5	¾

TOOL KIT SERIE FRH...KIT

Type FRH

Governor

Hose nipple

Retaining spring (A)

Retaining spring (B)

7 types of chisel

Metal case

