

GRINDER

BAHCO
DORTMUND



**PNEUMATIC VERTICAL
GRINDER SERIES FG**

BAHCO

BAHCO GmbH & Co.KG

Martener Hellweg 60

DE- 44379 Dortmund

Phone

+49 231/91 72 11-0

Fax

+49 231/91 72 11-22

www.bahco.de

info@bahco.de

All grinders are designed with the latest technology and manufactured grinder. The straight grinders are equipped with a governor, noise protection devices and a safety start lever.

These standard features provide a high performance and a smooth operation.



Dimensions

Type	Max. Ø grinding disc mm	Idle speed rpm	Spindle-thread-size Inch	Capacity kW	Total length mm	Weight kg	Max. air cons. m ³ /min	Comp. air connect. BSP o. NPT	Hose dia. mm / Inch	
Front air exhaust										
FG-3H-1F	65x13x 9.5	14600	W 3/8 - 16	0.48	342	1.7	0.55	3/8	9.5	3/8
FG-3H-2F	75x13x 9.5	12700	W 3/8 - 16	0.48	342	1.7	0.55	3/8	9.5	3/8
FG-4H-1F	100x19x 9.5	9500	W 3/8 - 16	0.70	408	2.3	0.80	3/8	12.7	1/2
FG-4H-2F	100x19x12.7	9500	W 1/2 - 12	0.70	414	2.3	0.80	3/8	12.7	1/2
FG-5H-1M	125x19x12.7	7600	W 1/2 - 12	0.96	506	2.5	1.00	3/8	12.7	1/2
FG-5H-2M	125x19x15.8	7600	5/8-11UNF	0.96	511	2.5	1.00	3/8	12.7	1/2
FG-6H-1M	150x25x15.8	6300	5/8-11UNF	1.03	531	3.4	1.20	3/8	12.7	1/2

Standard air connection: 3/8" BSP, FG-8H: 1/2" BSP.