

GRINDERS

BAHCO
DORTMUND



**PNEUMATIC EXTENDED
GRINDERS SERIES FG**

BAHCO

BAHCO GmbH & Co.KG

Martener Hellweg 60

DE- 44379 Dortmund

Phone

+49 231/91 72 11-0

Fax

+49 231/91 72 11-22

www.bahco.de

info@bahco.de

The extended grinders are perfect for grinding work in confined spaces or in pipes. The program includes a variety of grinders for various works.



FG-50L-1BF



FG-4HL-1F

Technical data

Type	Max. Ø grinding wheel mm	Idle speed min ⁻¹	Spindle thread size Zoll	Capacity kW	Total length mm	Weight kgs	Max. air consumption m ³ /min	Hose size mm inch	
Version with safety start lever									
FG-50L-1BF *	50x13x9.53	18,000	W 3/8 - 16	0.29	316	1.4	0.43	9.5	3/8
FG-50Y-1BF *	50x13x9.53	18,000	W 3/8 - 16	0.29	532	2.0	0.43	9.5	3/8
FG-3HL-1F	65x13x9.53	12,000	W 3/8 - 16	0.48	547	1.9	0.55	9.5	3/8
FG-4HL-1F	75x13x9.53	12,000	W 3/8 - 16	0.74	615	2.6	0.80	12.7	1/2
FG-5HL-2M	100x19x12.7	9,000	W 1/2 - 12	0.96	1,050	5.4	1.00	12.7	1/2

Series FG-50L, 50Y: Compressed air connection 1/4" BSP. Series FG-3HL, 4HL, 5HL: 3/8" BSP.

* with steel case



FG-26L-1BF

Extended version

Type	Collet size mm	Max. Ø grinding wheel mm	Milling pin mm	Idle speed min ⁻¹	Capacity kW	Total length mm	Weight kgs	Max. air consumption m ³ /min	Hose size mm inch	
Version with exhaust sideways										
FG-26L-1BF*	6	25	13	24,000	0.22	306	0.9	0.40	9.5	3/8
FG-26HL-1F	6	45	13	14,600	0.22	273	0.7	0.55	9.5	3/8
FG-3H-5F	6	50	25	14,600	0.48	367	1.5	0.55	9.5	3/8

* with steel case

Compressed air connection: 1/4" BSP, FG-3H-5: 3/8" BSP.

All information subject to change without further notice.
No responsibility is taken for the correctness of the named specifications.