

ACCESSORIES COMPRESSED AIR

BAHCO
DORTMUND



SAFETY COUPLINGS WITH VENTING FUNCTION + NIPPLES SERIES 320 eSAFE

- A safety coupling that vents before disconnection
- Extremely high flow capacity
- Easy handling and extreme durability

BAHCO

BAHCO GmbH & Co.KG

Martener Hellweg 60

DE- 44379 Dortmund

Phone






+49 231/91 72 11-0

Fax






+49 231/91 72 11-22

www.bahco.de

info@bahco.de

Couplings 	Part-No.	Connection
	10 320 2002	6,3 mm (1/4")
	10 320 2003	8,0 mm (5/16")
	10 320 2009	9,0 mm
	10 320 2004	10,0 mm (3/8")
	10 320 2005	13,0 mm (1/2")
	10 320 2152	R 1/4"
	10 320 2154	R 3/8"
	10 320 2155	R 1/2"
	10 320 2452	NPT 1/4"
	10 320 2454	NPT 3/8"
	10 320 2455	NPT 1/2"
	10 320 2202	G 1/4"
	10 320 2204	G 3/8"
	10 320 2205	G 1/2"
	10 320 2402	NPT 1/4"
	10 320 2404	NPT 3/8"
	10 320 2405	NPT 1/2"
	10 320 2058	5,0 x 8,0 mm
	10 320 2060	6,5 x 10,0 mm
	10 320 2062	8,0 x 12,0 mm
	10 320 2063	9,5 x 13,5 mm
	10 320 2066	11,0 x 16,0 mm

The coupling is an easy to use high performance shaft coupling with a long service life. It is a one-hand operated use safety coupling that vents before disconnection eliminating the risk of hose whip. Male threads on the couplings and nipples are factory-fitted with a thread sealing. The couplings have a smaller outside dimension than comparable designs. The fully automatic coupling ensures quick and easy handling.

Nipples 	Part-No.	Connection
	10 320 5001	5,0 mm (3/16")
	10 320 5002	6,3 mm (1/4")
	10 320 5003	8,0 mm (5/16")
	10 320 5004	10,0 mm (3/8")
	10 320 5005	13,0 mm (1/2")
	10 320 5151	R 1/8"
	10 320 5152	R 1/4"
	10 320 5154	R 3/8"
	10 320 5155	R 1/2"
	10 320 5451	NPT 1/8"
	10 320 5452	NPT 1/4"
	10 320 5201	G 1/8"
	10 320 5202	G 1/4"
	10 320 5204	G 3/8"
	10 320 5205	G 1/2"
	10 320 5401	NPT 1/8"
	10 320 5402	NPT 1/4"
	10 320 5404	NPT 3/8"
	10 320 5405	NPT 1/2"
	10 320 5058	5,0 x 8,0 mm
	10 320 5060	6,5 x 10,0 mm
	10 320 5062	8,0 x 12,0 mm
	10 320 5063	9,5 x 13,5 mm
	10 320 5066	11,0 x 16,0 mm

Technical data

Nominal width	7,6 mm
Flow capacity	2250 l/min.
Max. work. pressure	16 bar
Min. Bursting pressure	140 bar
Temperature range	-20°C bis +100°C
Coupling material	Steel/Brass, galvanized
Nipple material	Steel, hardened, galvanized
Coupling force	86 N
Outer diameter	23,5 mm

All information subject to change without further notice.
No responsibility is taken for the correctness of the named specifications.