

700 & 800 bar

BAHCO
DORTMUND



AIR-HYDRAULIC PUMPS SERIES PP 9200RC

The single stage air hydraulic pumps PP .. -9200 have a tank with large oil capacity and can be used with additional by mounted manifolds or valves for the operation of several hydraulic cylinders.

PP..-9200 is available in two different pressure ranges: 700 and 800 bar.

RC- 2.5 m Remote control with two buttons for extend, hold and release of single-acting cylinders.

A gauge, for example, AMT 801, can be mounted directly to the valve block. Hoses, couplings and pressure gauges see attachment.

BAHCO

BAHCO GmbH & Co.KG

Martener Hellweg 60

DE- 44379 Dortmund

Phone

+49 231/91 72 11-0

Fax

+49 231/91 72 11-22

www.bahco.de

info@bahco.de

Dimensions

Type	Max. Work pressure MPa	Eff. Oil volume cm ³	Capacity cm ³ /min	Required Air press. MPa	Length mm	Width mm	Height mm	Weight kgs
PP70A-9200RC	70	9200	1070-200	0.65-1.0	426	296	245	20
PP80A-9200RC	80	9200	710-130	0.6-1.0	426	296	245	20

Dimensions

Type	Max. Work press. MPa	Eff. Oil vol. cm ³	A mm	B mm	C mm	Pressure gauge M	P Hydr. Air connection	Air connection
PP70A-9200RC	70	9200	426	245	296	G 1/4"	G 1/4"	G 1/4"
PP80A-9200RC	80	9200	340	245	296	G 1/4"	G 1/4"	G 1/4"

Technical drawing

