

DRILLING MACHINES **BAHCO** DORTMUND



**STRAIGHT DRILLING MACHINE
SERIES FRD**

BAHCO



BAHCO GmbH & Co.KG

Martener Hellweg 60
DE- 44379 Dortmund

Phone

+49 231/91 72 11-0

Fax

+49 231/91 72 11-22

www.bahco.de

info@bahco.de

The drills are light but sturdy. Their practical design is the result of latest drill technology.

They offer a complete line of drills with a drilling capacity of 13 mm.

TECHNICAL DATA

Model	Drilling capacity	Torque	Idle speed	Type and size of thread	Chuck	Spindle center distance
	mm	Nm	min ⁻¹		mm	mm
FRD-5S-1F	6	2.0	3200	3/8" - 24	6.5	18.5
FRD-6S-2F	6	2.5	4300	3/8" - 24	6.5	21.0
FRD-6S-3F	8	2.9	2800	3/8" - 24	8.0	21.0
FRD-6S-5F	10	6.9	1300	3/8" - 24	10.0	23.0
•FRD-6S-7F	13	15.7	600	1/2" - 20	13.0	21.0

Model	Capacity	Total length	Weight	Max. air consumption
	kW	mm	kg	m ³ /min
FRD-5S-1F	0.18	175	0.6	0.60
FRD-6S-2F	0.29	209	0.9	0.68
FRD-6S-3F	0.29	212	1.0	0.68
FRD-6S-5F	0.29	233	1.0	0.68
•FRD-6S-7F	0.29	261	1.5	0.68

Compressed air connection 1/4" BSP.
Models with • have an auxiliary handle.

Delivered with keyed chuck and chuck key.
Also available with keyless (extra charge).

All information subject to change without further notice.
No responsibility is taken for the correctness of the named specifications.