

DRILLING MACHINES **BAHCO** DORTMUND



**PNEUMATIC DRILLING
MACHINE SERIE B-BL**

BAHCO

BAHCO GmbH & Co.KG

Martener Hellweg 60
DE- 44379 Dortmund

Phone

+49 231/91 72 11-0

Fax

+49 231/91 72 11-22

www.bahco.de

info@bahco.de

Drilling machines series B and BL have an inside sound absorber, with max. 75 dB (A).

The ergonomic handle ensures fatigue-proof drilling and high feed force.

Technical data

Type	Drilling	Torque	Idle speed	Type a. spindle size	Max. drilling	Spindle centre dist.	Capacity	Total length	Weight	Max. air consump.
	mm	Nm	rpm	thread	mm	mm	kW	mm	kgs	m³/min
B6-30	6	3.0	3000	3/8 - 24	6.5	19.0	0.25	145	0.65	0.36
B8-30	8	3.0	3000	3/8 - 24	8.0	19.0	0.25	155	0.70	0.36
B8S-30	8	3.0	3000	3/8 - 24	8.0	19.0	0.25	170	0.75	0.36
BL15-10	10	6.5	1500	3/8 - 24	10.0	21.5	0.37	180	1.05	0.60
BL15-10S	10	6.5	1500	3/8 - 24	10.0	21.5	0.37	200	1.20	0.60
•BL7-13	13	15.5	650	1/2 - 20	13.0	23.0	0.50	270	1.80	0.72
•BL7-13S	13	15.5	650	1/2 - 20	13.0	23.0	0.50	310	2.10	0.72
•BL3-16	16	20.0	320	1/2 - 20	16.0	23.0	0.50	280	2.10	0.72
•BL3-16S	16	20.0	320	1/2 - 20	16.0	23.0	0.50	300	2.40	0.72
•BL3-MK2	21	20.0	320	1/2 - 20	21.0	23.0	0.50	320	1.80	0.72

Compressed air connection: 1/4", Hose size B8-Series 1/4" (6.35mm), all other types 3/8" (9.5 mm)

Types with "S": Supplied with keyless chuck / Types with "MK2": Supplied with morse taper 2, Types SR 206-1

All other types: Supplied with keyed drill chuck and drill chuck key | Models with "•" have an extra handle



BL3-MK2



BL7-13



BL15-10



B-8-30

All information subject to change without further notice.
No responsibility is taken for the correctness of the named specifications.