

DRILLING MACHINES **BAHCO** DORTMUND



**DRILLING MACHINES WITH
PISTOL GRIP SERIES FRD**

BAHCO



BAHCO GmbH & Co.KG

Martener Hellweg 60

DE- 44379 Dortmund

Phone

+49 231/91 72 11-0

Fax

+49 231/91 72 11-22

www.bahco.de

info@bahco.de

The drills are light but robust. Their practical design is the result of the latest drill technology.

They offer a complete range of drills with a drilling capacity from 2 mm to 100 mm.

TECHNICAL DATA

Type	Drilling capacity	Torque	Idle speed	Type and size of thread		Chuck	Spindle center distance
	mm	Nm	min ⁻¹	Thread	Cone	mm	mm
FRD-6PH-2	6	2.7	4.300	–	JK#1	6.5	21.0
FRD-6PH-3	8	4.3	2.800	–	JK#1	8.0	21.0
FRD-6PH-5	10	7.5	1.300	–	JK#2S	10.0	21.0
•FRD-6PH-7	13	15.8	600	–	JK#6	13.0	22.5
FRD-8PX-1	8	5.9	2.600	3/8" - 24	—	8.0	25.0
•FRD-8PX-2	10	11.8	1.300	3/8" - 24	—	10.0	26.5
•FRD-8PX-3	13	16.7	900	1/2" - 20	—	13.0	25.5

TECHNICAL DATA

Type	Capacity	Total length	Weight	Max. air consumption	Hose size	
	kW	mm	kg	m ³ /min	mm	Inch
FRD-6PH-2	0.34	198	0.9	0.59	6.3	1/4"
FRD-6PH-3	0.34	205	1.0	0.59	9.5	3/8"
FRD-6PH-5	0.32	243	1.4	0.59	9.5	3/8"
•FRD-6PH-7	0.32	258	1.5	0.59	9.5	3/8"
FRD-8PX-1	0.44	187	1.5	0.76	9.5	3/8"
•FRD-8PX-2	0.44	210	1.9	0.76	9.5	3/8"
•FRD-8PX-3	0.44	240	2.5	0.76	9.5	3/8"

Compressed air connection 1/4" BSP. Models with „•“ have an auxiliary handle.
Delivered with keyed chuck and chuck key.
Also available with keyless (extra charge).

All information subject to change without further notice.
No responsibility is taken for the correctness of the named specifications.