


SAND RAMMER

BAHCO
DORTMUND



**PNEUMATIC SAND RAMMER
SERIES FR**

BAHCO

BAHCO GmbH & Co.KG

Martener Hellweg 60
DE- 44379 Dortmund

Phone

+49 231/91 72 11-0

Fax

+49 231/91 72 11-22

www.bahco.de

info@bahco.de

Molding sand rammers are powerful, yet easy for a travel range of 64 mm to 127 mm. The molding sand rammers are perfect for pounding the sand for molds in ferrous and non-ferrous foundries.

Dimensions

Type	Beats	Piston- dia. Ø	Stroke	Tamp. foot - dia. Ø	Total length	Weight	Air con. (under load)	Comp. air connec- tion	Hose width	
Starting safety lever	Hz	mm	mm	mm	mm	kg	m ³ /min	BSP	mm	Inch
FR-22B-2F	17	18.0	64	51	465	3.0	0.50	3/8	9.5	3/8
FR-25B-2F	13	25.4	83	67	630	5.5	0.70	3/8	12.7	1/2
FR-18L-2F	30	18.0	50	41	542	2.0	0.40	1/4	9.5	3/8
FR-22L-2F	17	22.0	64	51	614	3.3	0.50	1/4	9.5	3/8
FR-25L-2F	13	25.4	83	67	1038	6.0	0.70	1/2	12.7	1/2
FR-32-2F	12	32.0	127	75	1123	10.0	0.80	1/2	12.7	1/2

Delivery incl. tamping foot