

FINE GRINDER

BAHCO
DORTMUND



**PNEUMATIC FINE GRINDER
SERIES SF8**

BAHCO



BAHCO GmbH & Co.KG

Martener Hellweg 60

DE- 44379 Dortmund

Phone

+49 231/91 72 11-0

Fax

+49 231/91 72 11-22

www.bahco.de

info@bahco.de

Dimensions

Type	Collet size mm	Valve type	Max. grinding pin dia. Ø mm	Idle speed min ⁻¹	Capacity kW	Total length mm	Weight kg	Max. air consumption m ³ /min.
Front air exhaust								
SF8-FT	6/8	lever valve	32	20000	0.30	235	0.80	0.57
SF8-FK-1	6/8	rotary valve	32	20000	0.30	235	1.00	0.57
SF8-FTL •	6/8	lever valve	32	20000	0,30	275	0,85	0.57
SF8-FKL •	6/8	rotary valve	32	20000	0,30	275	1,00	0.57
Rear air exhaust, incl. supply and exhaust hose *								
SF8-BT	6/8	lever valve	32	20000	0.30	253	1.10*	0.57
SF8-BK	6/8	rotary valve	32	20000	0.30	253	1.15*	0.57
SF8-BTL •	6/8	lever valve	32	20000	0.30	293	1.15	0.57
SF8-BKL •	6/8	rotary valve	32	20000	0.30	293	1.25	0.57

Air connection: ¼", Hose dia. ⅜" (9.5 mm)

Standard-collet size: 6 mm

* Weight incl. supply and exhaust hose

See extra accessories catalog

• Phased-out model