

PNEUMATIC SCREWDRIVER

BAHCO
DORTMUND



**IMPULSE WRENCH
SERIES IPW + IPS
AUTO SHUT-OFF**

BAHCO

The impulse wrenches are equipped with an adjustable shut-off control, with double chamber motor and double blade impulse unit. The shut-off control is designed for a torque with a maximum deviation of $\pm 10\%$, depending on the screwdriving application.

The IPW and IPS series contribute to high productivity and improved quality in many industries.

The impulse wrenches have low reaction forces and can generate high torques without special support.

Straight Version



Technical data

Type	Square drive	Capacity bolt size	Torque range (5-6 bar)	Free speed	Overall length	Weight
	Inch	mm	Nm	min ⁻¹	mm	kg
with square drive						
IPW-2309B	3/8"	5	4 - 12	5400	218	0.83
IPW-2316B	3/8"	5 - 6	9 - 19	6400	218	0.83
IPW-2332B	3/8"	8	24 - 38	6200	228	0.87
IPW-2350B	3/8"	8 - 10	35 - 50	5800	241	0.95
IPW-2360B	3/8"	8 - 10	41 - 61	5900	247	1.20
IPW-2465B	1/2"	10	45 - 65	5900	252	1.25
with quick change						
IPS-2209	1/4"	5	4 - 12	5000	221	0.83
IPS-2216	1/4"	5 - 6	7 - 16	5400	221	0.83
IPS-2228	1/4"	6 - 8	21 - 34	6200	231	0.87
IPS-2232	1/4"	8	28 - 39	5800	241	0.95
IPS-2242	1/4"	8 - 10	35 - 45	5900	250	1.25

Compressed air connection: 1/4" PT

Hose size: IPW-2309/2316B as well as IPS-2209/2216 = 6.5 mm

Hose size: IPW-2332B till 2465B as well as IPS-2228/2232/2242 = 8.0 mm

Noise level: 75 - 84 dB(A)

SERIES IPW + IPS AUTO SHUT-OFF

BAHCO
DORTMUND

Pistol-Version



Technical data

Type	Square drive	Capacity bolt size	Torque range (5-6 bar)	Free speed	Overall length	Weight
	Inch	mm	Nm	min ⁻¹	mm	kg
with square drive						
IPW-2308PB	3/8"	5	4 - 12	4600	162	0.92
IPW-2316PB	3/8"	5 - 6	7 - 16	5100	162	0.92
IPW-2332PB	3/8"	8	24 - 38	6500	174	0.95
IPW-2350PB	3/8"	8 - 10	35 - 53	6500	180	1.05
IPW-2360PB	3/8"	8 - 10	40 - 60	5900	187	1.25
IPW-2465PB	1/2"	10	45 - 65	5900	186	1.25
IPW-2485PB	1/2"	10 - 12	60 - 85	5200	192	1.45
IPW-24115PB	1/2"	12	65 - 120	4700	198	1.70
IPW-24145PB	1/2"	12 - 14	110 - 155	4500	215	2.30
IPW-26200PB	3/4"	14 - 16	130 - 210	3800	240	2.90
IPW-26240PB	3/4"	16 - 18	170 - 270	3100	262	3.70
IPW-26450PB	3/4"	16 - 20	225 - 450	3200	221	4.20
with quick change chuck						
IPS-2209P	1/4"	5	4 - 12	4500	161	0.92
IPS-2216P	1/4"	5 - 6	8 - 18	5000	161	0.92
IPS-2230P	1/4"	6 - 8	21 - 34	6300	171	0.95
IPS-2232P	1/4"	8	28 - 39	6200	183	1.05
IPS-2242P	1/4"	8 - 10	38 - 47	5900	191	1.26

Compressed air connection: 1/4" PT

Hose size: IPW-2308PB/2316PB as well as IPS-2209P till 2230P = 6.5 mm

Hose size: IPW-2332PB till 24115PB as well as IPS-2242P = 8.0 mm

Hose size: IPW-26200PB/26240PB = 12.7 mm, IPW-26450PB = 13.0 mm

Noise level: 75 - 84 dB(A)



BAHCO GmbH & Co.KG

Martener Hellweg 60
DE- 44379 Dortmund

Phone

+49 231/91 72 11-0

Fax

+49 231/91 72 11-22

www.bahco.de

info@bahco.de

BAHCO

All information subject to change without further notice.
No responsibility is taken for the correctness of the named specifications.