

PNEUMATIC SCREWDRIVER

BAHCO
DORTMUND



**IMPULSE WRENCH IPW & IPS
WITH NON SHUT-OFF**

BAHCO

IMPULSE WRENCH IPW & IPS WITH NON SHUT-OFF

The impulse wrenches are equipped without adjustable shut-off control, with double chamber motor and double blade impulse unit. The IPW and IPS series contribute to high productivity and improved quality in many industries.

The impulse wrenches have low reaction forces and can generate high torques without special support.

Straight Version



Technical data

Type	Square drive	Screw size	Torque (5 - 6 bar)	Free speed	Overall length	Weight
	Inch	mm	Nm	min ⁻¹	mm	kg
with square drive						
IPW-2322NB	3/8"	5 - 6	13 - 22	5200	218.0	0.62
IPW-2335NB	3/8"	6 - 8	31 - 44	5800	218.0	0.74
IPW-2350NB	3/8"	8 - 10	42 - 57	5900	228.0	0.77
IPW-2360NB	3/8"	10	50 - 70	5700	241.0	0.87
IPW-2370NB	3/8"	10	60 - 90	5900	247.0	1.25
IPW-2480NB	1/2"	10 - 12	65 - 95	5900	252.0	1.25
with quick change chuck						
IPS-2220N	1/4"	5 - 6	14 - 22	5100	220.0	0.62
IPS-2228N	1/4"	6 - 8	18 - 28	5400	221.0	0.74
IPS-2235N	1/4"	8	35 - 42	5900	231.0	0.77
IPS-2240N	1/4"	8 - 10	36 - 46	5600	240.5	0.87
IPS-2260N	1/4"	8 - 10	45 - 60	6800	250.0	1.24

Compressed air connection: 1/4" PT

Hose size: IPW-2322NB / 2335NB as well as IPS-2220N / 2228N = 6.5 mm

Hose size: IPW-2350NB till 2480NB as well as IPS-2235N / 2240N / 2260N = 8.0 mm

Noise level: 75 - 84 dB(A)

IMPULSE WRENCH IPW & IPS WITH NON SHUT-OFF

BAHCO
DORTMUND

PISTOL VERSION



Technical data

Type	Square drive	Screw size	Torque (5-6bar)	Free speed	Overall length	Weight
	Inch	mm	Nm	min ⁻¹	mm	kg
with square drive						
IPW-2312PN	3/8"	5 - 6	9 - 18	4400	131.0	0.70
IPW-2322PNB	3/8"	6	17 - 30	4300	131.0	0.70
IPW-2335PN	3/8"	6 - 8	32 - 45	6000	134.0	0.77
IPW-2350PN	3/8"	8 - 10	46 - 60	6700	140.0	0.82
IPW-2360PN	3/8"	8 - 10	50 - 70	6800	155.0	0.95
IPW-2370PN	3/8"	10	65 - 95	6000	161.0	1.15
IPW-2380PN	1/2"	10 - 12	65 - 95	6000	167.0	1.17
IPW-2495PN	1/2"	12	100 - 120	5800	165.0	1.30
IPW-24125PN	1/2"	12 - 14	110 - 140	4500	172.0	1.66
IPW-24160PN	1/2"	14	120 - 165	4400	185.0	2.30
IPW-26230PN	3/4"	14 - 16	170 - 240	4200	213.5	2.50
IPW-26300PN	3/4"	16 - 18	230 - 290	3200	226.5	3.00
with quick change chuck						
IPS-2212PN	1/4"	5 - 6	8 - 17	4400	131.0	0.70
IPS-2220PN	1/4"	6	13 - 20	4000	131.0	0.70
IPS-2228PN	1/4"	6 - 8	18 - 30	6800	134.0	0.77
IPS-2235PN	1/4"	8	30 - 40	6500	142.0	0.82
IPS-2240PN	1/4"	8 - 10	42 - 50	6000	153.0	0.95
IPS-2260PN	1/4"	8 - 10	45 - 60	6800	170.0	1.20

Compressed air connection: 1/4" PT

Hose size: IPW-2312PN till 2335PN as well as IPS-2212PN till 2228PN = 6.5 mm

Hose size: IPW-2350PN till 24125PN as well as IPS-2235PN till 2240PN / 2260PN = 8.0 mm

Hose size: IPW-24160PN / 26230PN / 26300PN = 12.7 mm

Noise level: 75 - 84 dB(A)



BAHCO GmbH & Co.KG

Martener Hellweg 60
DE- 44379 Dortmund

Phone

+49 231/91 72 11-0

Fax

+49 231/91 72 11-22

www.bahco.de

info@bahco.de

BAHCO

All information subject to change without further notice.
No responsibility is taken for the correctness of the named specifications.