

SCREWING

TECHNOLOGY BATTERY TYPE

BAHCO
DORTMUND



CORDLESS
IMPACT WRENCH

BAHCO

EY 75A8 X/XT

- Low weight from 1.6 kg (incl. battery)
- ½ inch external square drive
- Brushless motor and electronic switch
- Electronic speed stabilisation
- Electronic run-out brake
- Belt holder and LED light



TECHNICAL DATA

Voltage	Charging time	Speed w/o load	Max. Torque [Nm]			Performance levels			Weight incl. battery
Volt	min.	min ⁻¹	Low	Medium	High	Low	Medium	High	kg
18	65 / 80	0 - 2500	120	140	280	3			from 1.60

EY 76A1 X/XT

- Brushless high-performance motor
- Hybrid switch
- 3 torque settings (low / medium / high)
- Battery charge level indicator and LED light
- Compact housing (127 mm), carbon design



TECHNICAL DATA

Voltage	Charging time	Speed w/o. load			Max. Torque [Nm]			Weight incl. battery
Volt	min.	min ⁻¹	min ⁻¹	min ⁻¹	Low	Medium	High	kg
18	65 / 80	0-2800	0-1450	0-950	26	150	170	1.70

TECHNICAL DATA

Number of hits		
Low	Medium	High
0 - 1800	0 - 2500	0 - 3100

EY 79A3 X/XT/PN2G/LJ2G

- Brushless high performance motor
- Thread cutting function
- Hybrid switch, soft start
- Extremely hard chuck
- Battery charge level indicator and LED light
- Compact housing (192 mm), carbon design



TECHNICAL DATA

Voltage	Charging time	Speed w/o. load			Max. Torque [Nm]			Weight incl. battery
Volt	min.	min ⁻¹	min ⁻¹	min ⁻¹	Low	Medium	High	kg
18	65 / 80	20-530	70-1800	32	50	400-9500	1260-32300	2.05

EY 7552 X/XT

- Low weight of 2.6 kg (incl. battery)
- Compact size: length 214 mm
- Maximum torque 470 Nm
- New double chamber design
- Variable speed control
- Electronic brake



TECHNICAL DATA

Voltage	Charging time	Speed w/o. load	Max. Torque	Hits/min. (M 12 Nut)	Weight incl. battery
Volt	min.	min ⁻¹	[Nm]		kg
18	65 / 80	0-1550	470	0-2400	ab 2.6

EY 7950 X/XT

- Low weight
- 18-stage clutch plus drill speed
- 13 mm heavy-duty drill chuck (keyless)
- Electronic speed stabilisation
- Electronic run-out brake, right/left rotation
- Safe front handle and LED light



TECHNICAL DATA

Voltage	Charging time	Speed w/o. load		Max. Torque [Nm]		Impact drilling function	Weight incl. battery
Volt	min.	Low	high	Soft	Hard	Hits/min.	kg
18	65 / 80	50-430	160-1650	40	57	7740 - 29700	from 2.3

BAHCO GmbH & Co.KG

Martener Hellweg 60
DE- 44379 Dortmund

Phone

+49 231/91 72 11-0

Fax

+49 231/91 72 11-22

www.bahco.de

info@bahco.de

BATTERIES AND CHARGING SYSTEMS



EY 0L82 B

- 14.4 - 28.8 volt quick charging system
inkl. 14.4 V / 1.5 Ah for all Li-Ionen-Battery types

18 V

5.0 Ah



EY 9L54 B

- Battery 18 Volt
- Li-Ionen-Battery with 5.0 Ah (according to IEC)

18 V

3.0 Ah



EY 9L53 B

- Battery 18 Volt
- Li-Ionen-Battery with 3.0 Ah (according to IEC)

The composition of complete sets is done by combining individual components.