

ACCESSORIES




BAHCO
DORTMUND





**MOUNTING PARTS FOR
CF/CFC-CYLINDER**





BAHCO

Dimensions

Model	for Cylinder	Type	Connection	
TC428 *	49 kN	Packing pin		
TD419 *	49 kN	Angle head for piston (max. 20 kN)	Cone Ø 19 mm	
TD420 *	49 kN	Angle head for cylinder (max. 20 kN)	Female, UN 1 ½-16	
TMC421 *	49 kN	Coupling piece	Cone Ø 19 mm	
TS430 *	49 kN	Support plate	Bore Ø 19 mm	

Model	for Cylinder	Type	Connection	
TC128 **	111 kN	Packing pin		
TD119 **	111 kN	Angle head for piston (max. 50 kN)	Female, NPT 1 ¼ - 11 ½	
TD120 **	111 kN	Angle head for cylinder (max. 50 kN)	Female, UN 2 ¼ - 14	

MOUNTING PARTS FOR CF/CFC-CYLINDER

Dimensions				
Model	for Cylinder	Type	Connection	
TMC121 **	111 kN	Coupling piece	Cone Ø 32 mm	
Model	for Cylinder	Type	Connection	
TMT122 **	111 kN	Double nipple	Male, 2x NPT 1¼ - 11½	
Model	for Cylinder	Type	Connection	
TMT124 **	111 kN	Coupling with female thread	Female, 2x NPT 1¼-11½	
Model	for Cylinder	Type	Connection	
TK107	111 kN	Chain (2m) with 1 hook		
Model	for Cylinder	Type	Connection	
TOK109 **	111 kN	Chain traverse	Female, UN 2 ¼ - 14	
Model	for Cylinder	Type	Connection	
TS130 **	111 kN	Support plate	Female, NPT1 ¼ - 11½	
Model	for Cylinder	Type	Connection	
TSM131 **	111 kN	Support plate with pivot pin	Male, NPT 1 ¼ - 11 ½	

* Using with pipe TFP103 or higher

BAHCO GmbH & Co.KG

Martener Hellweg 60
DE- 44379 Dortmund

Phone

+49 231/91 72 11-0

Fax


+49 231/91 72 11-22

www.bahco.de


info@bahco.de

Dimensions


Model	for Cylinder	Type	Connection
TC228 ***	232 kN	Locking pin	



Model	for Cylinder	Type	Connection
TMC221 ***	232 kN	Coupling piece	Cone Ø 48 mm



Model	for Cylinder	Type	Connection
TMT222 ***	232 kN	Double nipple	Male, 2x NPT 2 - 11 1/2



Model	for Cylinder	Type	Connection
TMT224 ***	232 kN	Coupling with female thread	Female, 2x NPT 2 - 11 1/2



Model	for Cylinder	Type	Connection
TS218 ***	232 kN	Support plate	Female, NPT 2 - 11 1/2

